## IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Previously Presented): An image processing apparatus operable to embed data into an image, said image comprising a frame of image data, said frame comprising first and second image fields generated from an inter-laced scan of the image, said apparatus comprising:

a combining processor operable to represent said data to be embedded in a transform domain form, and, in combination with a transform processor, to combine said data to be embedded with at least one of said first and second fields of said image in one of:

a transform domain form, said transform processor generating a transform domain form of said first and second fields, said data being combined with said first and second fields by said combining processor in said transform domain, or

a spatial domain form of said at least one of said first and second fields, said transform processor generating a spatial domain representation of said transform domain form of said data to be embedded, said data being combined with said at least one of said first and second fields of said image by said combining processor in said spatial domain,

wherein said transform domain provides a plurality of sub-bands and said combining processor is operable to combine data to be embedded with a first sub-band of said first field, and to combine said data with a second sub-band of said second field of said image data in said transform or said spatial domain, and

wherein said first sub-band and said second sub-band comprise mutually exclusive spatial frequency components.

2

Claim 2-3 (Canceled).

Claim 4 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 2, wherein said data embedded in said first sub-band includes first data and said data embedded in said second sub-band includes second data, said first and second data being different.

Claim 5 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 1, wherein said data embedded in said first sub-band and said data embedded in said second sub-band are the same data.

Claim 6 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 1, wherein said first sub-band in which said data is introduced into said first and second fields represents in said transform domain low spatial frequencies of said image in one direction and high spatial frequencies of said image in another direction, and

said second sub-band in which said data is introduced in said image frame represents in the transform domain high spatial frequencies of said image in said one direction and low spatial frequencies of said image in said another direction.

Claim 7 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 1, wherein said transform processor is operable in combination with said combining processor to introduce said data to be embedded into said image in accordance with the wavelet transform, of at least one of said data, said image frame and said at least one of said first and second fields, said wavelet transform providing said plurality of sub-bands.

Claim 8 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 7, wherein said first sub-band into which said data is introduced into said at least one of said first and second fields has one of low vertical, high horizontal frequencies and high vertical, low horizontal frequencies sub-bands, and said second sub-band into which said data is introduced into said image frame is the other of said low vertical, high horizontal frequencies and high vertical, low horizontal frequencies sub-bands.

Claim 9 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 8, wherein said data is introduced into said sub-bands in a scan direction, said scan direction being in the same direction in the sub-band as the direction of the low spatial frequencies of the image.

Claim 10 (Currently Amendment): [[An]] <u>The</u> image processing apparatus as claimed in Claim 1, comprising:

a modulator operable to modulate a Pseudo Random Symbol Stream with each of the data symbols to be embedded,

said modulated Pseudo Random Symbol Stream being introduced into said transform domain representation.

Claim 11 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 1, wherein said data is formed into first and second data sets, and said combining processor is operable to introduce said first and second data sets into said at least one of said first and second image fields of said image frame respectively.

Claim 12 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 11, wherein said data comprises data items, each data item and a copy of said each data item forming said first and said second data sets respectively.

Claim 13 (Currently Amended): [[An]] <u>The</u> image processing apparatus as claimed in Claim 12, wherein said data items to be embedded include a Unique Material Identifier (UMID).

Claim 14 (Currently Amended): [[An]] The image processing apparatus operable to detect and recover data embedded into an image by the image processing apparatus according to Claim 1, said apparatus comprising:

a data processor operable to identify at least one of first and second fields of said image into which data has been embedded;

a transform processor operable to generate a transform domain representation of said at least one of the first and second fields into which the data has been embedded; and

a data detector operable to detect and recover the data from said transform domain representation of said at least one of the first and second fields from the sub-bands into which the data has been embedded.

Claim 15 (Currently Amended): [[An]] <u>The</u> image processing apparatus as claimed in Claim 14, wherein said data detector is operable to combine first signals representative of the first data set recovered from said sub-band in said image fields, with second signals

representative of the second data set from said other sub-band in said image frame to form a composite signal from which said data items are recovered.

Claim 16 (Previously Presented): A method of embedding data into an image, said image comprising a frame of image data, said frame comprising first and second image fields generated from an inter-laced scan of the image, said method comprising:

representing said data to be embedded in a transform domain form;

combining said data to be embedded with at least one of said first and second fields of said image in one of:

a transform domain form, said data being combined with said first and second fields in said transform domain, or

a spatial domain form of said at least one of said first and second fields, by generating a spatial domain representation of said transform domain form of said data to be embedded, said data being combined with said at least one of said first and second fields of said image in said spatial domain,

wherein said transform domain provides a plurality of sub-bands and said combining comprises combining data to be embedded into a first sub-band of a transform domain representation of said first field and combining said data with a second sub-band of said second field of said image data in said transform or said spatial domain,

wherein said first sub-band and said second sub-band comprise mutually exclusive frequency components.

Claim 17 (Canceled).

Claim 18 (Currently Amended): [[A]] <u>The</u> method of detecting and recovering data embedded in an image by the image processing method according to Claim 16, said method further comprising:

identifying at least one of first and second fields of said image into which data has been embedded;

generating a transform domain representation of said at least one of the first and second fields into which the data has been embedded; and

detecting and recovering the data from said transform domain representation of said at least one of the first and second fields from the sub-bands into which the data has been embedded.

Claim 19 (Previously Presented): An apparatus for embedding data into an image, said image comprising a frame of image data, said frame comprising first and second image fields generated from an inter-laced scan of the image, said apparatus comprising:

means for representing said data to be embedded in a transform domain form;

means for combining said data to be embedded with at least one of said first and second fields of said image in one of:

a transform domain form, said data being combined with said first and second fields in said transform domain, or

a spatial domain form of said at least one of said first and second fields, by generating a spatial domain representation of said transform domain form of said data to be embedded, said data being combined with said at least one of said first and second fields of said image in said spatial domain,

wherein said transform domain provides a plurality of sub-bands and said means for combining is operable to combine data to be embedded with a first sub-band of said first field, and to combine said data with a second sub-band of said second field of said image data in said transform or said spatial domain, and

wherein said first sub-band and said second sub-band comprise mutually exclusive spatial frequency components.

Claim 20 (Currently Amended): [[An]] <u>The</u> apparatus for detecting and recovering data embedded in an image by the apparatus according to Claim 19, said apparatus further comprising:

means for identifying at least one of first and second fields of said image into which data has been embedded;

means for generating a transform domain representation of said at least one of the first and second fields into which the data has been embedded; and

means for detecting and recovering the data from said transform domain representation of said at least one of the first and second fields from the sub-bands into which the data has been embedded.

Claim 21 (Canceled).

Claim 22 (Currently Amended): [[A]] The computer program stored on a computer readable medium providing computer executable instructions, which when loaded on to a data processor configures said data processor to operate as an image processing apparatus as claimed in Claim 1.

Claim 23 (Currently Amended): [[A]] <u>The</u> computer program <u>stored on a computer</u> readable <u>medium</u> having computer executable instructions, which when loaded on to a data processor causes the data processor to perform the method according to Claim 16.

Claim 24 (Currently Amended): [[A]] <u>The</u> computer program product <u>having stored</u> on a computer readable medium having recorded thereon information signals representative of the computer program claimed in Claim 22.

Claim 25 (Currently Amended): [[A]] <u>The</u> computer product <u>having stored on</u> a computer readable medium having recorded thereon information signals representative of the computer program claimed in Claim 23.

Claim 26 (Previously Presented): An image processing apparatus operable to embed data into an image, said image comprising a frame of image data, said frame comprising first and second image fields generated from an inter-laced scan of the image, said apparatus comprising:

a combining processor operable to represent said data to be embedded in a transform domain form, and, in combination with a transform processor, to combine data to be embedded with at least one of said first and second fields of said image in one of:

a transform domain form, said transform processor generating a transform domain form of said first and second fields, said data being combined with said first and second fields by said combining processor in said transform domain, or

a spatial domain form of said at least one of said first and second fields, said transform processor generating a spatial domain representation of said transform domain form of said data to be embedded, said data being combined with said at least one of said first and second fields of said image by said combining processor in said spatial domain,

wherein said transform domain provides a plurality of sub-bands, said data to be embedded being introduced into at least one of said sub-bands of said at least one of said first and second fields of said image,

wherein said transform processor is operable in combination with said combining processor to introduce said data to be embedded into said image in accordance with the wavelet transform, of at least one of said data, said image frame and said at least one of said first and second fields, said wavelet transform providing said plurality of sub-bands,

wherein said first sub-band into which said data is introduced into said at least one of said first and second fields has one of low vertical, high horizontal frequencies and high vertical, low horizontal frequencies sub-bands, and said second sub-band into which said data is introduced into said image frame is the other of said low vertical, high horizontal frequencies and high vertical, low horizontal frequencies sub-bands,

wherein said data is introduced into said sub-bands in a scan direction, said scan direction being in the same direction in the sub-band as the direction of the low spatial frequencies of the image.

Claim 27 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 26, wherein said combining processor is operable to combine data to be embedded with a first sub-band of said first field, and to combine said data with a second sub-band of said second field of said image data in said transform or said spatial domain.

Claim 28 (Currently Amended): [[An]] <u>The</u> image processing apparatus as claimed in Claim 27, wherein said first sub-band and said second sub-band comprise mutually exclusive spatial frequency components.

Claim 29 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 27, wherein said data embedded in said first sub-band includes first data and said data embedded in said second sub-band includes second data, said first and second data being different.

Claim 30 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 27, wherein said data embedded in said first sub-band and said data embedded in said second sub-band are the same data.

Claim 31 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 26, wherein said first sub-band in which said data is introduced into said first and second fields represents in said transform domain low spatial frequencies of said image in one direction and high spatial frequencies of said image in another direction, and

said second sub-band in which said data is introduced in said image frame represents in the transform domain high spatial frequencies of said image in said one direction and low spatial frequencies of said image in said another direction.

Claim 32 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 26, comprising:

a modulator operable to modulate a Pseudo Random Symbol Stream with each of the data symbols to be embedded,

said modulated Pseudo Random Symbol Stream being introduced into said transform domain representation.

Claim 33 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 26, wherein said data is formed into first and second data sets, and said combining processor is operable to introduce said first and second data sets into said at least one of said first and second image fields of said image frame respectively.

Claim 34 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 33, wherein said data comprises data items, each data item and a copy of said each data item forming said first and said second data sets respectively.

Claim 35 (Currently Amended): [[An]] The image processing apparatus as claimed in Claim 34, wherein said data items to be embedded include a Unique Material Identifier (UMID).

Claim 36 (Currently Amended): [[An]] The image processing apparatus operable to detect and recover data embedded into an image by the image processing apparatus according to Claim 26, said apparatus comprising:

a data processor operable to identify at least one of first and second fields of said image into which data has been embedded;

a transform processor operable to generate a transform domain representation of said at least one of the first and second fields into which the data has been embedded; and

a data detector operable to detect and recover the data from said transform domain representation of said at least one of the first and second fields from the sub-bands into which the data has been embedded,

wherein said data detector is operable to combine first signals representative of the first data set recovered from said sub\_band in said image fields, with second signals representative of the second data set from said other sub-band in said image frame to form a composite signal from which said data items are recovered.

Claim 37 (Previously Presented): A method of embedding data into an image, said image comprising a frame of image data, said frame comprising first and second image fields generated from an inter-laced scan of the image, said method comprising:

representing said data to be embedded in a transform domain form;

combining said data to be embedded with at least one of said first and second fields of said image in one of:

a transform domain form, said data being combined with said first and second fields in said transform domain, or

a spatial domain form of said at least one of said first and second fields, by generating a spatial domain representation of said transform domain form of said data to be embedded, said data being combined with said at least one of said first and second fields of said image in said spatial domain,

wherein said transform domain provides a plurality of sub-bands and said data to be embedded is combined into at least one of said sub-bands, said data being combined with said at least one of said first and second fields of said image in said sub-band of said fields,

said method comprises combining data to be embedded into a first sub-band of a transform domain representation of said first field; and

combining said data with a second sub-band of said second field of said image data in said transform or said spatial domain,

wherein said combining includes introducing said data to be embedded into said image in accordance with the wavelet transform, of at least one of said data, said image frame and said at least one of said first and second fields, said wavelet transform providing said plurality of sub-bands,

wherein said first sub-band into which said data is introduced into said at least one of said first and second fields having one of low vertical, high horizontal frequencies and high vertical, low horizontal frequencies sub-bands, and said second sub-band into which said data is introduced into said image frame being the other of said low vertical, high horizontal frequencies and high vertical, low horizontal frequencies sub-bands,

wherein said data being introduced into said sub-bands in a scan direction, said scan direction being in the same direction in the sub-band as the direction of the low spatial frequencies of the image.

Claim 38 (Canceled).

Claim 39 (Currently Amended): [[A]] <u>The</u> computer program product <u>stored on a</u> <u>computer readable medium</u> providing computer executable instructions, which when loaded

Application No. 10/006,329 Reply to Office Action of March 9, 2006

on to a data processor configures said data processor to operate in accordance with the method according to Claim 27.